



Sportsliter

IP55

Sportsliter is designed for use with 1kW and 1.5kW metal halide lamps and remote control gear. The optics offer Nema 2 to 6 beam distributions, making it suitable for floodlighting many sports and recreational venues.

Applications

- Sports Lighting
- Container Terminals
- Bulk Storage Yards
- Railway Sidings
- Community Pools
- Large Buildings



Top Visor




4090 Bracket



4024C Spigot Mount




Photometric design data



Horizontal illumination – Sportsliter SLSN5

Mounting height – 18.0m Area – 48m x 48m
 X increments = 8.0m Y increments = 8.0m
 Plane height = 0.0m Aiming angle – 60°
 Windage – 0.30 m² Weight – 8.2 kg



Horizontal illumination – Sportsliter SLSN2

Mounting height – 18.0m Area – 48m x 48m
 X increments = 8.0m Y increments = 8.0m
 Plane height = 0.0m Aiming angle – 60°
 Windage – 0.30 m² Weight – 8.2 kg

See page 99 for remote control gear options.
 Not suitable for ground mounting

Product reference

Lamp and control gear ordered separately

SLSN2	20°	MI1500/BU	MI1000/U
SLSN3	34°	MI1500/BU	MI1000/U
SLSN4	68°	MI1500/BU	MI1000/U
SLSN5	86°	MI1500/BU	MI1000/U
SLSN6	114°	MI1500/BU	MI1000/U

Accessories

SL-HCL	half concentric louve
SL-CL	full concentric louve
SL-SV	top visor
4024C	60mm slipfitter spigot
4090	cross arm mounting bracket

